



**SPE RUSSIAN PETROLEUM
TECHNOLOGY CONFERENCE
AND EXHIBITION**

24-26 October 2016
WTC, Moscow, Russia

SPE-181928-MS.

Well Drilling Process Optimization in the Verkhnechonskoye Oil and Gas Condensate Field

Andrey Dubrovin, Andrey Klabukov, Nikolay Abaltusov, Weatherford.
Vladimir Shulga, PAO"VCNG"




Society of Petroleum Engineers

Verkhnechonskoye Oil and Gas Condensate Field




- VCOGCF is located in the north of the Irkutsk Region, in the Chone river's head
- It is one of the largest in Eastern Siberia
- Oil reserves total 200 million tons
 - Gas reserves total 95.5 billion m³


Verkhnechonskoye Oil and Gas Condensate Field




VCOGCF Geological Structure




Pay Formations in VCOGCF




Well Drilling Process Optimization in VCOGCF



Production Casing Section Drilling



Experiment #1. Drilling over 2 Runs



Production Casing Section Drilling over 1 run

Water based mud




Oil based mud



Stator elastomer wears out much faster



Motor with an oil-resistant elastomer is required




Motor with an Oil-Resistant Elastomer



Drilling mud samples




Motor manufacturing




NBR-HR-37 elastomer

Experiment #2. Drilling over 1 Run



Time for Drilling Production Casing Section



Conventional drilling of production casing section

Drilling over 2 runs


12-30 h

Drilling over 1 run



≈ 45 hours

Restrictions

Azimuth change is to be less than 60°




Production casing setting depth is to be less than 2700 m



The Results of Production Casing Section Drilling Optimization

- ✓ LWD suite is included in BHA
- ✓ Production casing section is drilled per one run
- ✓ The bit design is optimized
- ✓ An optimal size of the motor stabilizer is selected
- ✓ Water based mud is replaced by oil based mud
- ✓ Oil resistant elastomer is selected based on drilling fluid sampling
- ✓ MWD pulser is adjusted based on defined borehole conditions
 - Data transmission speed increase
 - ROP increase

Record well



Production casing interval is drilled and cased for **7 days**

Total well construction time
14 days

The Results of Production Casing Section Drilling Optimization

- ✓ 8 wells drilled with Drilling optimization
- ✓ 250 hrs of total well-construction time saving
- ✓ 15 000 000 RUB – Value to Client



**SPE RUSSIAN PETROLEUM
TECHNOLOGY CONFERENCE
AND EXHIBITION**

24-26 October 2016
WTC, Moscow, Russia

Acknowledgements / Thank You / Questions

The authors express thanks to the management groups of PAO “VCNG” (PAO “NK Rosneft”) and Weatherford companies for the permission to publish and submit the results of this paper.

We also express thanks to the drilling crew and the service specialists who were involved in the well drilling and were gathering the field data for analysis.

